



"The first thing that struck me was the naturalness of the presentation."\*



"It doesn't draw attention to itself, it just gets on with its job and does very well indeed."\*



"You immediately notice the shed-load of power on offer."\*

\*Excerpts from reviews in Hi-Fi Choice, UK

## 2010S Compact Disc Player

- 1 Single PCM 1716 24 bit DAC fitted to provide very high resolution
- 2 CD display can be turned off for improved sound quality
- 3 Highly optimised audio output circuitry with multiple stages of supply regulation
- 4 Large toroidal power transformer with separate windings for CD transport mechanism and audio stages
- 5 Employment of a high-stability crystal clock reference and dedicated, improved power supply regulator for the transport and audio stages to ensure low jitter performance
- 6 High quality double-sided PCBs for optimum layout and screening
- 7 Improved all-aluminium casework and extruded front panel to control resonance and stray electro-magnetic fields
- 8 Full-function remote control
- 9 Three-year guarantee

## 2010S Integrated Amplifier

- 1 High capacity, 200VA custom-made toroidal power transformer and power supply capacitors
- 2 Improved all-aluminium casework and extruded front panel to control resonance and stray electro-magnetic fields
- 3 High quality capacitors used in the signal path
- 4 Uniquely tuned short signal and power supply path PCB
- 5 Cascode circuitry utilised for improved power supply immunity
- 6 Sanken bipolar output transistors for dynamics and performance
- 7 Separate pre-amp output
- 8 Bi-wiring compatible
- 9 75 watts per channel into 8 ohms
- 10 Improved system remote control
- 11 Three-year guarantee

## 2010S Power Amplifier

- 1 High capacity 200VA custom-made toroidal power transformer and supply capacitors
- 2 Improved all-aluminium casework and extruded front panel to control resonance and stray electro-magnetic fields
- 3 High quality capacitors used in the signal path
- 4 Very clean and extended low frequency performance
- 5 Bi-Wiring compatible and switchable to mono block mode thereby doubling output current for low impedance loads
- 6 75 watts per channel into 8 ohms
- 7 Three-year guarantee

"The 2010S (CD player) is up there with the best in its class. Fabulous treble, great dynamics and a weighty yet solid bottom-end make for a superb CD player."

"Exposure kit tends to put performance above flashy cosmetics and features. The 2010S (integrated amplifier) is a powerful, straight-talking amp that trades in some of the refinement and insight of the class leaders for a sizeable dose of fun. If you just want to sit back and enjoy music, give it a whirl."

*UK-based Exposure Electronics Ltd has been engineering real hi-fi at real-world prices since 1974. It is Exposure's commitment to consistently create quality high fidelity equipment which out-perform their price tags for the global market.*

What Hi-Fi, Ultimate Guides Hi-Fi, 2006



*exposure*<sup>TM</sup>  
high fidelity engineering since 1974

*exposure*<sup>TM</sup>  
high fidelity engineering since 1974

# 2010S

# 2010S

### 2010S CD Player

- Output Level: 2V RMS
- Frequency Response: 20Hz - 20KHz  $\pm$  0.03dB
- Total Harmonic Distortion: <0.008%, 20Hz - 20KHz, 0dBFs
- Signal to Noise Ratio: >100dB, A weighted
- Digital Outputs: SP/DIF, Coaxial and "Toslink" Optical
- Mains Supply: 110/120V or 220/240V, 50/60Hz (factory set)
- Power Consumption: 25 Watts
- Dimensions - H x W x D: 90 mm x 440 mm x 300 mm
- Nett Weight (unpacked): 5kg
- Gross Weight (packed): 7kg

### 2010S Integrated Amplifier

- Power Output (1KHz): 75 Watts per channel RMS 8 Ohms
- Input Sensitivity: 250mV
- Input Impedance: >14K Ohms, line input
- Pre-amplifier Output: gain + 18dB
- Frequency Response: 20Hz - 20KHz  $\pm$  0.5dB
- Total Harmonic Distortion: <0.05% at 1KHz, rated power
- Signal to Noise: >100dB, A weighted, ref rated output
- Channel Separation: 20Hz - 20KHz, >60dB
- Mains Supply: 110/120V or 220/240V, 50/60Hz (factory set)
- Max Power Consumption: 200VA (both channels driven, 8 Ohms load)
- Dimensions - H x W x D: 90 mm x 440 mm x 310 mm
- Nett Weight (unpacked): 7kg
- Gross Weight (packed): 9kg

### 2010S Power Amplifier

- Power Output (Stereo): 75 Watts per channel at 1KHz into 8 Ohms
- Input Sensitivity: 1V, gain +24dB
- Input Impedance: >18K Ohms
- Frequency Response: 20Hz - 20KHz  $\pm$  0.5dB
- Total Harmonic Distortion: <0.02% at 1KHz, rated power
- Signal to Noise: >110dB, A weighted, ref rated output
- Channel Separation: >80dB, 20Hz - 20KHz
- Mains Supply: 110/120V or 220/240V, 50/60Hz (factory set)
- Power Consumption: 200VA, both channels driven, 8 Ohms load
- Dimensions - H x W x D: 90 mm x 440 mm x 310 mm
- Nett Weight (unpacked): 7kg
- Gross Weight (packed): 9kg

Exposure Electronics Ltd:  
The Works 59 North Street, Portslade,  
East Sussex BN41 1DH, England.  
Tel: +44 1273 423877 Fax: +44 1273 430619

[www.exposurehifi.com](http://www.exposurehifi.com)

In line with Exposure's policy of continuous improvement, we reserve the right to change technical specifications without prior notice.

*real hi-fi at real-world prices*

